



PRODUCT DATA SHEET

VAPO-KLEEN™

HIGH PERF. PREMIUM LPG/PROPANE TANK CLEANING ADDITIVE with CH25X Technology (VAPOKLEEN)

APPLICATIONS

VAPO-KLEEN™ can be used as part of a maintenance program to remove and prevent deposits occurring in both direct and indirect LP-gas vaporizers and downstream in regulators and valves. VAPO-KLEEN™ can also be used to clean tanks and lines. VAPO-KLEEN™ is documented to improve the quality of LPG/Propane used in all types of propane applications. Typical applications include direct & indirect LP-gas vaporizers in process systems, standby systems, peak-load systems, grain dryers, boilers, heaters, dryers and any propane powered fuel systems.

BLENDING RECOMMENDATIONS

Product can be added to bulk propane storage during delivery of fuel. Storage tank should have a 20% heel of fuel and be free of excess water and/or sludge.

Treat Rate

1:3000

Maximum Dosage: Dosage for this product should not exceed 1 gallon per 1000 gallons of propane.

Additive performance depends on the specific fuel being treated and condition of storage tanks.

SAFETY PRECAUTIONS

When handling this product, persons should exercise caution and wear protective goggles, gloves and clothing. See cautions indicated in the corresponding Safety Data Sheet before handling and storing this product.

WARRANTY

We guarantee this product to comply with our published specifications. Since the use of this product is beyond our control, we disclaim responsibility for its performance, handling, use, storage, the results obtained, or any injury of any nature resulting there from. Product warrantee and seller's obligations apply only to replacement of product. Seller assumes no liability for any claim or loss of any other kind. In no event shall seller be liable for indirect punitive, special or consequential damages or expenses. Any warrantee claim shall be governed by and construed in accordance with the laws and jurisdiction of the State of Illinois.

TYPICAL SPECIFICATIONS

Color (ASTM D1544)..... Blue
Specific Gravity @ 68° F (ASTM D891)..... 0.797
Density, lbs./gal. (Calculated)6.65
Flash Point °F, TCC (ASTM D3278).....109
Additive Pour Point °F (ASTM D97)..... N/A
Viscosity @ 68° F cP (Brookfield)..... N/A

This product is ashless and contains no heavy metals, metallic compounds or alcohol.

PACKAGING

Available in bulk, 300 gal. totes, 55 gal. and 2.5 gal. containers.

© 2018 ValvTect Petroleum Products, 1608 Barclay Blvd., Buffalo Grove, IL 60089 ▪ Phone: (800) 728-8258 ▪ Fax: (847) 272-4260

ValvTect®, Lumin™, & VAPO-KLEEN™ are trademarks of ValvTect Petroleum Products. CH25X is a trademark of Guardian Protection Products, Inc.

VAPOKLEENPDS0118-2